


## Cuscinetti conico 2984A-2924-TIMKEN - 2984A-2924-TIMKEN

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rulli/conico/2984a-2924-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE ROW • TYPE TS

**TYPE TS**



| Bearing Dimensions |                  |                  | Load Ratings                          |                         |                                       |                         |                       |                 | Part Number |      |
|--------------------|------------------|------------------|---------------------------------------|-------------------------|---------------------------------------|-------------------------|-----------------------|-----------------|-------------|------|
| Bore d             | O.D. D           | Width B          | Dynamic <sup>(1)</sup> C <sub>1</sub> | Factor <sup>(2)</sup> e | Dynamic <sup>(3)</sup> C <sub>2</sub> | Factor <sup>(3)</sup> K | Static C <sub>0</sub> | Inner           | Outer       |      |
| mm                 | mm               | mm               | N                                     |                         | N                                     |                         | N                     |                 |             |      |
| 46.037<br>1.8125   | 85.000<br>3.3465 | 25.400<br>1.0000 | 3200<br>2100                          | 3.22<br>1.73            | 34200<br>5400                         | 14300<br>3225           | 1.68<br>1.67          | 117000<br>25000 | 2984A       | 2924 |

| Bearing Dimensions |                  |                          |   |   |  |   |                               |                               |                               | Geometry Factors |                |                | Bearing Weight |      |
|--------------------|------------------|--------------------------|---|---|--|---|-------------------------------|-------------------------------|-------------------------------|------------------|----------------|----------------|----------------|------|
| Shaft              |                  |                          |   |   | Housing                                    |   |                               |                               |                               | Cage             |                |                |                |      |
| Width B            | Width C          | ER. Dr. α <sup>(1)</sup> | Max Shaft Fillet Radius R <sub>f</sub> <sup>(2)</sup> | Backing Shoulder Dia. d <sub>s</sub> <sup>(3)</sup> | Max Housing Fillet Radius r <sup>(4)</sup> | Backing Shoulder Dia. D <sub>s</sub> <sup>(5)</sup> | A <sub>1</sub> <sup>(6)</sup> | A <sub>2</sub> <sup>(7)</sup> | A <sub>3</sub> <sup>(8)</sup> | G <sub>1</sub>   | G <sub>2</sub> | C <sub>3</sub> | kg             |      |
| mm                 | mm               | mm                       | mm  | mm  | mm   | mm  | mm                            | mm                            | mm                            |                  |                |                | lb             |      |
| 25.400<br>1.0000   | 25.400<br>0.8125 | -4.4<br>-0.25            | 0.8<br>0.03   | 52.0<br>2.05  | 53.0<br>2.09                               | 1.3<br>0.05   | 80.0<br>3.15                  | 76.0<br>2.98                  | 1.7<br>0.07                   | 1.1<br>0.05      | 38.2           | 15.7           | 0.8622         | 0.62 |

### CARATTERISTICHE DEL PRODOTTO

|                  |               |
|------------------|---------------|
| Marchio          | TIMKEN        |
| N° Ean13         | 3663952314976 |
| Diametro interno | 46.037 mm     |
| Diametro interno | 1 13/16" inch |
| Diametro esterno | 85 mm         |
| Diametro esterno | 3.346" inch   |
| Spessore         | 25.4 mm       |
| Spessore         | 1" inch       |
| Imballaggio      | 1             |

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE