Cuscinetti conico
XAE32010X-32010X-TIMKEN - XAE32010X-32010X-TIMKEN

https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rulli/conico/xae32010x-32010x-timken



TAPERED ROLLER BEARINGS

SINGLE-ROW • IsoClass

IsoClass

Bearing Dimensions																												Part Number
Bore d	O.D. D	Width T	Load Ratings																									Assembly Inner/Outer
			Dynamic[1] C_1	Factors[2] e	Y	Y_0	Dynamic[3] C_{90}	C_{u90}	Factors[2] K	Static C_0																		
mm in.	mm in.	mm in.	N lbf				N lbf	N lbf		N lbf																		
50.000 1.9685	80.000 3.1496	20.000 0.7874	82700 18600	0.42		1.42	21500 4820	15500 3490	1.38	92700 20800																		XAE32010X/32010X

Bearing Dimensions														Geometry Factors			Bearing Weight
			Shaft			Housing			Cage								
Width B	Width C	Eff. Ctr $a^{(4)}$	Max Shaft Fillet Radius $R^{(5)}$	Backing Shoulder Dia. d_a	d_b	Max Housing Fillet Radius $r^{(5)}$	Backing Shoulder Dia. D_a	D_b	$A_s^{(6)}$	$A_h^{(7)}$				G_1	G_2	C_g	
mm in.	mm in.	mm in.	mm in.	mm in.	mm in.	mm in.	mm in.	mm in.	mm in.	mm in.							kg lbs.
20.000 0.7874	15.500 0.6102	-2.0 -0.08	0.3 0.01	55.0 2.17	56.0 2.20	1.0 0.04	77.0 3.03	73.0 2.87	0.9 0.03	2.1 0.08				34.0	20.3	0.0853	0.36 0.82

123BEARING

CARATTERISTICHE DEL PRODOTTO

Marchio	TIMKEN
N° Ean13	3663952332048
Diametro interno	50 mm
Diametro esterno	80 mm
Spessore	20 mm
Imballaggio	1

contatto@123cuscinetti.it
+33 3 59 36 04 90
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE