

Cuscinetti a sfera fila unica ZKLN1034-2Z-INA - ZKLN1034-2Z-INA

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-sfera-fila-unica/zkln1034-2z-ina>

Axial angular contact ball bearings ZKLN1034-2Z
double direction, gap seals on both sides

d	10 mm	Tolerance: -0.005
D	34 mm	Tolerance: -0.010
B	20 mm	Tolerance: -0.25
α	60 °	Contact angle
D _{u,max}	28 mm	
d _u	21 mm	
d _{u,rot}	14 mm	
r _{1,rot}	0,6 mm	
r _{2,rot}	0,3 mm	
m	0,1 kg	Mass
C _u	13400 N	Basic dynamic load rating, axial
C _{0u}	10000 N	Basic static load rating, axial
n _{lim,grease}	6000 1/min	Limiting speed for grease lubrication
M _{lim,grease}	0,08 Nm	Bearing frictional torque
C _u	325 N/mm	Axial rigidity
α _{tilt}	25 Nm/rad	Tilting rigidity
M _u	0,029 kg x cm ²	Mass moment of inertia for rotating inner ring
r _{ax}	2 μm	Axial runout
		The axial runout data for screw drive bearing arrangements are based on the rotating inner ring.
ZM10		Designation of recommended INA locknut
		Locknuts not included in delivery.
M _s	8 Nm	Tightening torque
		Only valid in conjunction with INA precision locknuts
F _{ax}	4891 N	Axial preload force

CARATTERISTICHE DEL PRODOTTO

Marchio	INA
N° Ean13	3663952334837
Diametro interno	10 mm
Impermeabilizzazione	Schermo su entrambi i lati
Diametro esterno	34 mm
Spessore	20 mm
Peso	100 g
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE