

Cuscinetti a sfera fila unica ZKLN70120-2Z-INA - ZKLN70120-2Z-INA

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-sfera/fila-unica/zkln70120-2z-ina>

Axial angular contact ball bearings ZKLN70120-2Z	
double direction, gap seals on both sides	
	d 70 mm Tolerance: -0.008
	D 120 mm Tolerance: -0.015
	B 45 mm Tolerance: -0.25
	α 60 ° Contact angle
	D_{1max} 110 mm
	d_1 95 mm
	d_2 92 mm
	r_{1max} 0.6 mm
	r_{2max} 0.6 mm
	m 2.4 kg Mass
	C_a 85000 N Basic dynamic load rating, axial
	C_{0a} 281000 N Basic static load rating, axial
	$n_{lim,grease}$ 2300 1/min Limiting speed for grease lubrication
	M_{fr} 1.2 Nm Bearing frictional torque
	S_a 1400 N/mm Axial rigidity
	c_a 2250 Nmm/rad Tilting rigidity
	M_{j2} 19.8 kg x cm ² Mass moment of inertia for rotating inner ring
	r_a 3 µm Axial runout
	The axial runout data for screw drive bearing arrangements are based on the rotating inner ring.
	ZMA70110 Designation of recommended INA locknut
	AM70 Designation of recommended INA locknut
	Locknuts not included in delivery.
	M_t 130 Nm Tightening torque
	Only valid in conjunction with INA precision locknuts
	F_{ax} 19171 N Axial preload force

CARATTERISTICHE DEL PRODOTTO

Marchio	INA
N° Ean13	3663952334974
Diametro interno	70 mm
Impermeabilizzazione	Schermo su entrambi i lati
Diametro esterno	120 mm
Spessore	45 mm
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE