


## Cuscinetti conico 3474-3420-B-TIMKEN - 3474-3420-B-TIMKEN

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rulli/conico/3474-3420-b-timken>

**TAPERED ROLLER BEARINGS**

**TYPE TSF**



Bearing Dimensions				Load Ratings						Part Number	
Bore d	O.D. D	Width B		Dynamic <sup>(1)</sup> C <sub>1</sub>	Factors <sup>(2)</sup> e	Y	Dynamic <sup>(1)</sup> C <sub>2</sub>	Factors <sup>(2)</sup> K	Static C <sub>3</sub>	Inner	Outer
mm	mm	mm		N			N		N		
30.162	79.375	10.320		10500	0.33	1.34	27100	17000	13000	3474	3420-B
1.1875	3.1250	0.4083		23000			6100	3620	26000		

Bearing Dimensions				Shaft			Housing		Geometry Factors			Bearing Weight
Width B	Width C	Eff. Ctr. a <sup>(1)</sup>	Outer Ring Range D <sub>1</sub> D <sub>2</sub>	Flange Width C <sub>1</sub>	Max Shaft File Radius (R <sup>(1)</sup> )	Sealing Shoulder Dia. d <sub>1</sub>	Sealing Shoulder Dia. d <sub>2</sub>	Geometry Factors	G <sub>1</sub>	G <sub>2</sub>	C <sub>3</sub>	kg
mm	mm	mm	mm	mm	mm	mm	mm					lbs.
20.771	23.812	-4.6	94.000	4.762	0.8	40.0	43.0	70.0	29.9	11.2	0.0181	0.76
1.1721	0.9375	-0.34	3.3000	0.1875	0.03	1.57	1.61	2.99				1.72

### CARATTERISTICHE DEL PRODOTTO

Marchio	TIMKEN
N° Ean13	3663952335667
Diametro interno	30.162 mm
Diametro interno	1 3/16" inch
Diametro esterno	79.375 mm
Diametro esterno	3 1/8" inch
Spessore	10.32 mm
Spessore	13/32" inch
Imballaggio	1

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE