


## Cuscinetti conico 3381-3320-B-TIMKEN - 3381-3320-B-TIMKEN

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rulli/conico/3381-3320-b-timken>

**TAPERED ROLLER BEARINGS**  
**TYPE TSF**



| Bearing Dimensions |          |             |  | Load Ratings                    |                               |      |                                    |                               |                 | Part Number |        |
|--------------------|----------|-------------|--|---------------------------------|-------------------------------|------|------------------------------------|-------------------------------|-----------------|-------------|--------|
| Bore $d$           | O.D. $D$ | Width $T_1$ |  | Dynamic <sup>(1)</sup><br>$C_1$ | Factors <sup>(2)</sup><br>$e$ | $Y$  | Dynamic <sup>(1)</sup><br>$C_{10}$ | Factors <sup>(2)</sup><br>$K$ | Static<br>$C_0$ | Inner       | Outer  |
| mm                 | mm       | mm          |  | N                               |                               |      | N                                  |                               | N               |             |        |
| 38.130             | 80.167   | 10.320      |  | 115000                          | 0.27                          | 2.20 | 22000                              | 13000                         | 12000           | 3381        | 3320-B |
| 1.500              | 3.182    | 0.408       |  | 25000                           |                               |      | 6700                               | 3100                          | 25100           |             |        |

| Bearing Dimensions |           |                     |                                 | Shaft              |                                   |                             |                             | Housing                     |       | Geometry Factors |        |      | Bearing Weight |
|--------------------|-----------|---------------------|---------------------------------|--------------------|-----------------------------------|-----------------------------|-----------------------------|-----------------------------|-------|------------------|--------|------|----------------|
| Width $B$          | Width $C$ | Eff. Ctr. $a^{(3)}$ | Outer Ring Range D <sub>1</sub> | Flange Width $C_1$ | Max Shaft Fillet Radius $R^{(4)}$ | Sealing Shoulder Dia. $d_1$ | Sealing Shoulder Dia. $d_2$ | Sealing Shoulder Dia. $D_1$ | $G_1$ | $G_2$            | $C_2$  |      |                |
| mm                 | mm        | mm                  | mm                              | mm                 | mm                                | mm                          | mm                          | mm                          |       |                  |        | kg   |                |
| 38.301             | 23.812    | -18.0               | 84.026                          | 4.202              | 3.3                               | 14.5                        | 91.8                        | 77.8                        | 24.8  | 12.1             | 0.0144 | 0.75 |                |
| 1.500              | 0.9375    | -0.43               | 3.3368                          | 0.1675             | 0.14                              | 1.75                        | 2.01                        | 3.03                        |       |                  |        | 1.63 |                |

### CARATTERISTICHE DEL PRODOTTO

|                  |               |
|------------------|---------------|
| Marchio          | TIMKEN        |
| N° Ean13         | 3663952336480 |
| Diametro interno | 38.1 mm       |
| Diametro esterno | 80.167 mm     |
| Spessore         | 10.32 mm      |
| Imballaggio      | 1             |

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE