


## Cuscinetti conico 3877-3820-B-TIMKEN - 3877-3820-B-TIMKEN

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rulli/conico/3877-3820-b-timken>

**TAPERED ROLLER BEARINGS**

**TYPE TSF**



Bearing Dimensions				Load Ratings						Part Number	
Bore d	O.D. D	Width B	Dynamic <sup>(1)</sup> C <sub>1</sub>	Factors <sup>(2)</sup> e	Dynamic <sup>(1)</sup> C <sub>2</sub>	Factors <sup>(2)</sup> e	Static C <sub>0</sub>	Inner	Outer		
mm	mm	mm	N		N		N				
41.275	85.725	11.112	124800	0.40	22200	22200	1.45	148000	3877	3820-B	
1.6250	3.3750	0.4375	27900		7740	4860		32000			

Bearing Dimensions				Shaft			Housing		Geometry Factors			Bearing Weight
Width B	Width C	Eff. Ctr. a <sup>(3)</sup>	Outer Ring Range D <sub>1</sub> D <sub>2</sub>	Flange Width C <sub>1</sub>	Max Shaft File Radius R <sup>(4)</sup>	Sealing Shoulder Dia. d <sub>1</sub>	Sealing Shoulder Dia. d <sub>2</sub>	Sealing Shoulder Dia. D <sub>1</sub>	D <sub>1</sub>	D <sub>2</sub>	C <sub>1</sub>	kg
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm
30.162	23.812	-4.1	80.586	4.202	3.3	36.6	37.8	83.8	37.8	13.5	0.2673	0.66
1.1875	0.9375	-0.32	3.2075	0.1675	0.14	1.46	1.50	3.24				1.81

### CARATTERISTICHE DEL PRODOTTO

Marchio	TIMKEN
N° Ean13	3663952336886
Diametro interno	41.275 mm
Diametro interno	1 5/8" inch
Diametro esterno	85.725 mm
Diametro esterno	3 3/8" inch
Spessore	30.162 mm
Spessore	1 3/16" inch
Imballaggio	1

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE