


Gusci a rullini YT1715-IKO - YT1715-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/gusci-rullini/yt1715-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS



Shaft dia. mm	Identification number									
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained	Mass (Ref.) g
17	---	---	---	---	---	---	---	---	YT 1715	20.5

Boundary dimensions mm		Standard mounting dimensions mm						Basic dynamic load rating	Basic static load rating	Allowable rotational speed ^(*)	Assembled inner ring		
F_w	D	C	f_2 Max.	Shaft dia. d_1 Max.	Shaft dia. d_1 Min.	Housing bore dia. D_1 Max.	Housing bore dia. D_1 Min.	C	C_0	rpm	IRT 1215-2		
17	24	15	---	17.000	16.989	24.012	23.991	---	---	16 600	26 000	9 000	IRT 1215-2

Note(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 80% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952353135
Diametro interno	17 mm
Diametro esterno	24 mm
Spessore	15 mm
Peso	22 g
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE