

## Cuscinetti conico 32956-TIMKEN - 32956-TIMKEN

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rulli/conico/32956-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • IsoClass

**IsoClass**

| Bearing Dimensions |         |         | Load Ratings                          |                         |                                       |                         |                       |                      | Part Number |  |
|--------------------|---------|---------|---------------------------------------|-------------------------|---------------------------------------|-------------------------|-----------------------|----------------------|-------------|--|
| Bore d             | O.D. D  | Width T | Dynamic <sup>(1)</sup> C <sub>1</sub> | Factor <sup>(2)</sup> e | Dynamic <sup>(3)</sup> C <sub>2</sub> | Factor <sup>(3)</sup> K | Static C <sub>0</sub> | Assembly Inner/Outer |             |  |
| mm                 | mm      | mm      | N                                     |                         | N                                     |                         | N                     |                      |             |  |
| in                 | in      | in      | lbf                                   |                         | lbf                                   |                         | lbf                   |                      |             |  |
| 280.000            | 380.000 | 63.500  | 850000                                | 0.43                    | 220000                                | 102000                  | 1700000               | 32956                |             |  |
| 11.0236            | 14.9608 | 2.5000  | 191000                                |                         | 49000                                 | 36700                   | 4010000               |                      |             |  |

  

| Mounting Dimensions |         |                         |  |                                      |  |                                      |                                      |                               |                               | Geometry Factors |                |                | Bearing Weight |                |
|---------------------|---------|-------------------------|--|--------------------------------------|--|--------------------------------------|--------------------------------------|-------------------------------|-------------------------------|------------------|----------------|----------------|----------------|----------------|
| Shaft               |         |                         |  |                                      | Housing                                    |                                      |                                      |                               |                               | Cage             | G <sub>1</sub> | G <sub>2</sub> |                | C <sub>3</sub> |
| Width B             | Width C | ER Co. a <sup>(4)</sup> | Max Shaft Fillet Radius R <sup>(5)</sup> | Backing Shoulder Dia. d <sub>s</sub> | Max Housing Fillet Radius r <sup>(6)</sup> | Backing Shoulder Dia. D <sub>s</sub> | Backing Shoulder Dia. D <sub>1</sub> | A <sub>1</sub> <sup>(7)</sup> | A <sub>2</sub> <sup>(8)</sup> |                  |                |                | G <sub>1</sub> |                |
| mm                  | mm      | mm                      | mm                                       | mm                                   | mm   | mm                                   | mm                                   | mm                            | mm                            | mm               | mm             | mm             | kg             |                |
| in                  | in      | in                      | in                                       | in                                   | in   | in                                   | in                                   | in                            | in                            | in               | in             | in             | lbs            |                |
| 63.500              | 40.000  | 11.4                    | 3.8                                      | 298.0                                | 300.0                                      | 2.5                                  | 100.0                                | 206.1                         | 7.5                           | 3.4              | 100.5          | 238.2          | 0.1000         | 10.6           |
| 2.5000              | 1.5748  | 0.45                    | 0.15                                     | 11.85                                | 11.81                                      | 0.10                                 | 3.94                                 | 8.12                          | 0.29                          | 0.14             | 3.94           | 9.45           | 0.0035         | 0.23           |

### CARATTERISTICHE DEL PRODOTTO

|                  |                  |
|------------------|------------------|
| Marchio          | TIMKEN           |
| N° Ean13         | 3663952354194    |
| Diametro interno | 280 mm           |
| Diametro interno | 11.024" inch     |
| Diametro esterno | 380 mm           |
| Diametro esterno | 14.961" inch     |
| Spessore         | 63.5 mm          |
| Spessore         | 2 1/2" inch      |
| Imballaggio      | 1                |
| Standard         | Nessuno standard |

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE