


## Cuscinetti conico 25570-25520D-TIMKEN - 25570-25520D-TIMKEN

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rulli/conico/25570-25520d-timken>

**TAPERED ROLLER BEARINGS**  
DOUBLE-ROW • TYPE TDO

**TYPE TDO**



| Bearing Dimensions |        |         |                           | Load Ratings           |      |                       |      |                        |                 |                       |      |                       |   |
|--------------------|--------|---------|---------------------------|------------------------|------|-----------------------|------|------------------------|-----------------|-----------------------|------|-----------------------|---|
| Bore d             | O.D. D | Width T | Double Outer Ring Width C | Dynamic <sup>(1)</sup> |      | Static <sup>(2)</sup> |      | Dynamic <sup>(3)</sup> |                 | Static <sup>(3)</sup> |      | Factor <sup>(4)</sup> |   |
| mm                 | mm     | mm      | mm                        | C <sub>10</sub>        | C    | N <sub>10</sub>       | N    | C <sub>90</sub>        | C <sub>50</sub> | C <sub>100</sub>      | N    | N                     | K |
| 36.512             | 82.931 | 57.150  | 47.625                    | 10000                  | 36.5 | 2320                  | 2320 | 22500                  | 13000           | 40000                 | 1.34 |                       |   |
| 1.4375             | 3.265  | 2.2500  | 1.8750                    | 38.400                 |      |                       |      | 870                    | 3020            | 9180                  |      |                       |   |

| Part Number |        | Dimensions                              |                                      |   |                                      |                |                | Pin            |                | Geometry Factors |                |      | Bearing Weight |
|-------------|--------|---|--------------------------------------|---|--------------------------------------|----------------|----------------|----------------|----------------|------------------|----------------|------|----------------|
| Inner       | Outer  | Max. Shaft Fillet Radius R <sub>1</sub> | Backing Shoulder Dia. d <sub>1</sub> | Max. Housing Fillet Radius r <sub>1</sub> | Backing Shoulder Dia. D <sub>1</sub> | K <sub>1</sub> | K <sub>2</sub> | G <sub>1</sub> | G <sub>2</sub> | C <sub>1</sub>   | C <sub>2</sub> |      |                |
| 25570       | 25520D | 3.5<br>0.14                             | 91.8<br>2.81                         | 8.8<br>0.55                               | 77.8<br>3.05                         | -              | -              | 35.2           | 14.3           | 0.0801           | 1.53           | 3.38 |                |

### CARATTERISTICHE DEL PRODOTTO

|                  |               |
|------------------|---------------|
| Marchio          | TIMKEN        |
| N° Ean13         | 3663952355177 |
| Diametro interno | 36.512 mm     |
| Diametro interno | 1 7/16" inch  |
| Diametro esterno | 82.931 mm     |
| Diametro esterno | 3.265" inch   |
| Spessore         | 57.15 mm      |
| Spessore         | 2 1/4" inch   |
| Imballaggio      | 1             |

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE