

Gusci a rullini TAW5545-Z-IKO - TAW5545-Z-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/gusci-rullini/taw5545-z-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS



Shaft dia. mm	Identification number								
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained (Ref.) g
55	TAW 5545 Z	250	—	—	—	—	—	—	—

Boundary dimensions mm		Standard reporting dimensions mm						Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ^(*) rpm	Assembled inner ring		
F _w	D	C	f ₂ Max.	Shaft dia. h8		Housing bore dia. H7		N	N	5 500	IRT 5045-1		
				Min.	Max.	Min.	Max.						
55	67	45	3.4	55.000	54.981	67.018	66.988	—	—	79 900	172 000	5 500	IRT 5045-1

Note(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 80% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952357379
Diametro interno	55 mm
Diametro esterno	67 mm
Spessore	45 mm
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE