

## Gusci a rullini TA7040-Z-IKO - TA7040-Z-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/gusci-rullini/ta7040-z-iko>

**IKO**  
**SHELL TYPE NEEDLE ROLLER BEARINGS**



Shaft dia. mm	Identification number									
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained	Mass (Ref.) g
70	TA 7040 Z	290	—	—	—	—	—	—	—	—

  

Boundary dimensions mm		Standard mounting dimensions mm						Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed <sup>(*)</sup>	Assembled inner ring
F <sub>w</sub>	D	C	f <sub>2</sub> Max.	Shaft dia. H7 Max. Min.	Housing bore dia. H7 Max. Min.	N7 Max. Min.	N	N	rpm	IRT 6040	
70	82	40	3.4	70.000	69.981 82.022 81.987	—	—	92 000	222 000	3 500	IRT 6040

Note(\*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 80% of this value is allowable.  
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

### CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952357546
Diametro interno	70 mm
Diametro interno	2.756" inch
Diametro esterno	82 mm
Diametro esterno	3.228" inch
Spessore	40 mm
Spessore	1.575" inch
Imballaggio	1

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE