


## Cuscinetti conico

### 95500-95927CD-TIMKEN - 95500-95927CD-TIMKEN

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rulli/conico/95500-95927cd-timken>

**TAPERED ROLLER BEARINGS**  
DOUBLE-ROW • TYPE TDO

**TYPE TDO**



| Bearing Dimensions |         |         |                           | Load Ratings           |        |                       |      |                        |        |                       |        |
|--------------------|---------|---------|---------------------------|------------------------|--------|-----------------------|------|------------------------|--------|-----------------------|--------|
| Bore d             | O.D. D  | Width T | Double Outer Ring Width C | Dynamic <sup>(1)</sup> |        | Static <sup>(2)</sup> |      | Dynamic <sup>(3)</sup> |        | Factor <sup>(4)</sup> |        |
| mm                 | mm      | mm      | mm                        | C <sub>10</sub>        | N      | C <sub>0</sub>        | N    | C <sub>90</sub>        | N      | C <sub>50</sub>       | K      |
| in                 | in      | in      | in                        |                        |        |                       |      |                        |        |                       |        |
| 127.000            | 234.568 | 142.875 | 114.300                   | 100000                 | 380000 | 0.57                  | 1.83 | 2.72                   | 163000 | 100000                | 294000 |
| 5.000              | 9.250   | 5.625   | 4.500                     |                        |        |                       |      |                        | 30700  | 23200                 | 83600  |

| Part Number |         | Dimensions                              |                                      |   |                                      |                |                | Pin            |                | Geometry Factors |                |       | Bearing Weight |
|-------------|---------|---|--------------------------------------|---|--------------------------------------|----------------|----------------|----------------|----------------|------------------|----------------|-------|----------------|
| Inner       | Outer   | Max. Shaft Fillet Radius R <sub>1</sub> | Backing Shoulder Dia. d <sub>1</sub> | Max. Housing Fillet Radius r <sub>1</sub> | Backing Shoulder Dia. D <sub>1</sub> | K <sub>1</sub> | K <sub>2</sub> | G <sub>1</sub> | G <sub>2</sub> | C <sub>1</sub>   | C <sub>2</sub> |       |                |
| mm          | mm      | mm                                      | mm                                   | mm  | mm                                   | mm             | mm             | mm             | mm             | mm               | mm             | kg    |                |
| 95500       | 95927CD | 6.4                                     | 154.8                                | 1.5                                       | 217.8                                | 22.23          | 8.73           | 453.9          | 151.4          | 0.1323           | 26.36          | 26.36 |                |
|             |         | 0.25                                    | 6.09                                 | 0.06                                      | 8.54                                 | 0.88           | 0.34           |                |                |                  |                | 59.88 |                |

## CARATTERISTICHE DEL PRODOTTO

|                  |               |
|------------------|---------------|
| Marchio          | TIMKEN        |
| N° Ean13         | 3663952359649 |
| Diametro interno | 127 mm        |
| Diametro esterno | 234.95 mm     |
| Spessore         | 142.875 mm    |
| Imballaggio      | 1             |

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE