

Gusci a rullini YB2-5-4-IKO - YB2-5-4-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/gusci-rullini/yb2-5-4-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series

Shaft dia. mm (inch)	Identification number			Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained (Ref.) g	Mass (Ref.) g
	Standard	Mass (Ref.) g	Closed end										
3.969 ($\frac{3}{16}$)	—	—	—	YB 2.5 4	—	—	—	—	—	—	—	—	—

Boundary dimensions			Standard mounting dimensions				Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ^(*)	Assembled inner ring
F _w	D	C	Shaft dia. h8	Housing bore dia. J7	h ₂	h ₁				
3.969	7.144	6.35	3.969	3.961	7.152	7.137	2 320	2 440	40 000	—

Note^(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952361192
Diametro interno	3.969 mm
Diametro esterno	7.144 mm
Spessore	6.35 mm
Peso	96 g
Imballaggio	1
Standard	Nessuno standard

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE