


Gusci a rullini YB55-IKO - YB55-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/gusci-rullini/yb55-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number										
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g		
7.938 ($\frac{5}{16}$)	—	—	—	—	YB 55	3.8	—	—	—		
Boundary dimensions mm(inch)		Standard mounting dimensions mm				Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽¹⁾	Assembled inner ring		
F _w	D	C	b ₂ Max.	h ₈ Max.	J7 Min.	N	N	rpm			
7.938 $\frac{1}{16}$	12.700 $\frac{1}{2}$	7.921 $\frac{5}{16}$	—	7.938	7.929	12.710	12.692	5 110	6 090	20 000	—

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952361222
Diametro interno	7.938 mm
Diametro esterno	12.7 mm
Spessore	7.92 mm
Peso	4 g
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE