


Gusci a rullini YB68-IKO - YB68-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/gusci-rullini/yb68-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number			Identification number			Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ^(*) rpm	Assembled inner ring	
	Standard	Mass (Ref.) g	Closed end	Standard	Mass (Ref.) g	Closed end					Mass (Ref.) g
9.525 ($\frac{3}{8}$)	—	—	—	YB 68	7.2	—	—	—	—	—	
Boundary dimensions mm(inch)		Standard mounting dimensions mm		Basic dynamic load rating		Basic static load rating		Allowable rotational speed ^(*)		Assembled inner ring	
F _w	D	C	h ₂ Max.	h ₂ Min.	Housing bore dia. J7 Max.	Housing bore dia. J7 Min.	N	N	rpm		
9.525 ($\frac{3}{8}$)	14.288 ($\frac{1}{2}$)	12.70 (500)	—	9.525	9.516	14.298	14.280	9 210	13 600	16 000	—

Note^(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952361253
Diametro interno	9.525 mm
Diametro esterno	14.288 mm
Spessore	12.7 mm
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE