


Gusci a rullini BHAM1612-IKO - BHAM1612-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/gusci-rullini/bham1612-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number										
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g		
25.400 (1)	—	—	—	—	—	—	—	BHAM 1612	37	—	—
Boundary dimensions mm(inch)			Standard mounting dimensions mm				Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ^(*)	Assembled inner ring	
<i>F_w</i>	<i>D</i>	<i>C</i>	<i>t</i>	Shaft dia. h _s	Housing bore dia. J7	Max.	Min.	N	N	rpm	
25.400	33.338	19.05	3.4	25.400	25.387	33.352	33.327	19 900	29 700	15 000	IRB 1212

Note^(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952362014
Diametro interno	25.4 mm
Diametro interno	1" inch
Diametro esterno	33.338 mm
Diametro esterno	1 5/16" inch
Spessore	19.05 mm
Spessore	3/4" inch
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE