


Gusci a rullini BHAM1616-IKO - BHAM1616-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/gusci-rullini/bham1616-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Standard			Closed end			Identification number			Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ^(*) rpm	Assembled inner ring
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g				
25.400 (1)	—	—	—	—	—	—	—	BHAM 1616	48	—	—	—	
Boundary dimensions mm(inch)													
F_w	D	C	t	Shaft dia. mm		Housing bore dia. mm		Basic dynamic load rating C		Basic static load rating C ₀		Assembled inner ring	
25.400	33.338	25.40(1.000)	3.4	Max.	Min.	Max.	Min.	N	N	rpm	IRB 1216		

Note^(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952362038
Diametro interno	25.4 mm
Diametro esterno	33.338 mm
Spessore	25.4 mm
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE