


Gusci a rullini YB1816-IKO - YB1816-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/gusci-rullini/yb1816-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number			Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained	Mass (Ref.) g
	Standard	Mass (Ref.) g	Closed end										
28.575 (1 1/8)	—	—	—	—	—	—	—	—	—	—	—	YB 1816	51.5
Boundary dimensions mm(inch)			Standard mounting dimensions mm			Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽¹⁾ rpm	Assembled inner ring				
F _w	D	C	Shaft dia. h6 Max. Min.	Housing bore dia. J7 Max. Min.	Max. Min.								
28.575 1 1/8	34.925 1 1/4	25.40 1.000	28.575 28.562	34.939 34.914	38 700	90 400	5 500	IRB 1416					

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952362083
Diametro interno	28.575 mm
Diametro esterno	34.925 mm
Spessore	25.4 mm
Peso	53 g
Imballaggio	-
Standard	Nessuno standard

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE