


## Gusci a rullini BHAM2020-IKO - BHAM2020-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/gusci-rullini/bham2020-iko>

**IKO**  
**SHELL TYPE NEEDLE ROLLER BEARINGS**  
Inch Series



Shaft dia. mm (inch)	Identification number										
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g		
31.750 (1 1/4)	—	—	—	—	—	—	—	<b>BHAM 2020</b>	86.5	—	—

Boundary dimensions			Standard mounting dimensions				Basic dynam.	Basic static	Allowable	Assembled	
$F_w$	$D$	$C_0$	Shaft dia. $d_s$	Housing bore dia. $d_H$	Basic dynam. load rating $C$	Basic static load rating $C_0$	Allowable rotational speed <sup>(*)</sup>	Assembled inner ring			
mm	mm	mm	Max.	Min.	Max.	Min.	N	N	rpm		
31.750 (1 1/4)	41.275 (1 1/2)	31.75 (1.250)	3.4	31.750	31.734	41.289	41.264	40 000	69 600	12 000	IRB 1620

Note<sup>(\*)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

## CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952362335
Diametro interno	31.75 mm
Diametro esterno	41.275 mm
Spessore	31.75 mm
Imballaggio	1

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE