


Gusci a rullini YB2610-IKO - YB2610-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/gusci-rullini/yb2610-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number			Standard			Mass (Ref.)			Grease retained g	Mass (Ref.) g
	Standard	Mass (Ref.) g	Closed end	Standard	Mass (Ref.) g	Closed end	Standard	Mass (Ref.) g	Closed end		
41.275 (1 5/8)	—	—	—	—	—	—	—	—	—	—	YB 2610 69

Boundary dimensions			Standard mounting dimensions				Basic dynamic load rating C	Basic static load rating C0	Allowable rotational speed ⁽¹⁾ rpm	Assembled inner ring
F _w	D	C	Shaft dia. h8 Max.	Housing bore dia. J7 Min.	Max.	Min.				
41.275 (1 5/8)	50.800 2	15.88 (625)	41.275	41.259	50.818	50.788	37 000	71 700	3 500	IRB 2210

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952363219
Diametro interno	41.275 mm
Diametro esterno	50.8 mm
Spessore	15.88 mm
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE