


## Cuscinetti conico

### L217845D-L217810-TIMKEN - L217845D-L217810-TIMKEN

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rulli/conico/l217845d-l217810-timken>

**TAPERED ROLLER BEARINGS**  
DOUBLE-ROW • TYPE TDI

**TYPE TDI**



| Bearing Dimensions |         |         |                           | Load Ratings                          |                                     |                                     |                                     |                                     |                                       |                                      |                        |                                       |                                     |                        |
|--------------------|---------|---------|---------------------------|---------------------------------------|-------------------------------------|-------------------------------------|-------------------------------------|-------------------------------------|---------------------------------------|--------------------------------------|------------------------|---------------------------------------|-------------------------------------|------------------------|
| Bore d             | O.D. D  | Width T | Double Inner Ring Width B | Dynamic <sup>CR</sup> C <sub>10</sub> | Static <sup>CR</sup> C <sub>0</sub> | Factor <sup>CR</sup> Y <sub>1</sub> | Factor <sup>CR</sup> Y <sub>2</sub> | Factor <sup>CR</sup> Y <sub>3</sub> | Dynamic <sup>CR</sup> C <sub>90</sub> | Static <sup>CR</sup> C <sub>50</sub> | Factor <sup>CR</sup> K | Dynamic <sup>CR</sup> C <sub>10</sub> | Static <sup>CR</sup> C <sub>0</sub> | Factor <sup>CR</sup> K |
| mm                 | mm      | mm      | mm                        | N                                     | N                                   |                                     |                                     |                                     | N                                     | N                                    |                        | N                                     | N                                   |                        |
| 85.725             | 123.825 | 41.278  | 44.480                    | 17000                                 | 35000                               | 0.3                                 | 2.1                                 | 3.1                                 | 26000                                 | 12000                                | 41000                  | 17000                                 | 35000                               | 1.77                   |
| 3.3750             | 4.8750  | 1.6251  | 1.7500                    |                                       |                                     |                                     |                                     |                                     | 5400                                  | 3050                                 | 9400                   |                                       |                                     |                        |

| Part Number |         | Dimensions                 |                                      |  |                                      | Geometry Factors |                |                | Bearing Weight |
|-------------|---------|----------------------------|--------------------------------------|--|--------------------------------------|------------------|----------------|----------------|----------------|
| Inner       | Outer   | Max Shaft Fillet Radius BH | Backing Shoulder Dia. e <sub>s</sub> | Max Housing Fillet Radius r <sup>H</sup> | Backing Shoulder Dia. D <sub>s</sub> | G <sub>1</sub>   | G <sub>2</sub> | C <sub>3</sub> | kg             |
| mm          | mm      | mm                         | mm                                   | mm                                       | mm                                   |                  |                |                | lbm            |
| L217845D    | L217810 | 0.8                        | 38.8                                 | 1.5                                      | 116.8                                | 111.3            | 74.8           | 0.1152         | 1.74           |
|             |         | 0.03                       | 3.85                                 | 0.05                                     | 4.57                                 |                  |                |                | 3.85           |

## CARATTERISTICHE DEL PRODOTTO

|                  |               |
|------------------|---------------|
| Marchio          | TIMKEN        |
| N° Ean13         | 3663952368559 |
| Diametro interno | 85.725 mm     |
| Diametro esterno | 123.825 mm    |
| Spessore         | 41.278 mm     |
| Peso             | 1740 g        |
| Imballaggio      | 1             |

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE