


Cuscinetti conico

52400D-52618-TIMKEN - 52400D-52618-TIMKEN

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rulli/conico/52400d-52618-timken>

TAPERED ROLLER BEARINGS
DOUBLE-ROW • TYPE TDI

TYPE TDI



| Bearing Dimensions | | | | Load Ratings | | | | | | | | |
|--------------------|---------|---------|---------------------------|--|--------------------------------------|-------------------------------------|-------------------------------------|---------------------------------------|---------------------------------------|---------------------------------------|------------------------|------|
| Bore d | O.D. D | Width T | Double Inner Ring Width B | Dynamic ¹⁾ C ₁₀₂ | Static ²⁾ C ₀₂ | Factor ³⁾ Y ₁ | Factor ³⁾ Y ₂ | Dynamic ⁴⁾ C ₉₀ | Dynamic ⁴⁾ C ₅₀ | Static ⁴⁾ C ₁₀₀ | Factor ⁵⁾ K | |
| mm | mm | mm | mm | N | N | N | N | N | N | N | | |
| 101.600 | 157.162 | 80.167 | 79.375 | 30500 | 87500 | 0.5 | 1.4 | 2.1 | 5700 | 4700 | 10100 | 1.23 |
| 4.930 | 6.1875 | 3.1562 | 3.1250 | | | | | 1300 | 1050 | 2270 | | |

| Part Number | | Dimensions | | | | Geometry Factors | | | Bearing Weight |
|-------------|-------|--|--------------------------------------|--|--------------------------------------|------------------|----------------|----------------|----------------|
| Inner | Outer | Max Shaft Fillet Radius r _H | Backing Shoulder Dia. s ₁ | Max Housing Fillet Radius r _H | Backing Shoulder Dia. s ₂ | G ₁ | G ₂ | C ₃ | kg |
| mm | mm | mm | mm | mm | mm | | | | lbm |
| 52400D | 52618 | 1.5 | 112.4 | 3.3 | 142.8 | 175.4 | 41.7 | 0.1019 | 6.29 |
| | | 0.08 | 4.43 | 0.13 | 5.59 | | | | 11.87 |

CARATTERISTICHE DEL PRODOTTO

| | |
|------------------|---------------|
| Marchio | TIMKEN |
| N° Ean13 | 3663952368627 |
| Diametro interno | 101.6 mm |
| Diametro esterno | 157.162 mm |
| Spessore | 80.167 mm |
| Imballaggio | 1 |

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE