


## Cuscinetti conico

### 74510D-74850-TIMKEN - 74510D-74850-TIMKEN

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rulli/conico/74510d-74850-timken>

**TAPERED ROLLER BEARINGS**  
DOUBLE-ROW • TYPE TDI

**TYPE TDI**



| Bearing Dimensions |         |         |                           | Load Ratings                           |                                      |                                     |                                     |                                       |                                       |  |                        |      |
|--------------------|---------|---------|---------------------------|--|--------------------------------------|-------------------------------------|-------------------------------------|---------------------------------------|---------------------------------------|--|------------------------|------|
| Bore d             | O.D. D  | Width T | Double Inner Ring Width B | Dynamic <sup>1)</sup> C <sub>102</sub> | Static <sup>2)</sup> C <sub>02</sub> | Factor <sup>3)</sup> Y <sub>1</sub> | Factor <sup>3)</sup> Y <sub>2</sub> | Dynamic <sup>4)</sup> C <sub>90</sub> | Dynamic <sup>4)</sup> C <sub>50</sub> | Dynamic <sup>4)</sup> C <sub>100</sub> | Factor <sup>5)</sup> K |      |
| mm                 | mm      | mm      | mm                        | N                                      | N                                    | N                                   | N                                   | N                                     | N                                     | N                                      |                        |      |
| 130.005            | 215.900 | 123.825 | 123.825                   | 60500                                  | 132200                               | 0.5                                 | 1.4                                 | 2.1                                   | 80000                                 | 62000                                  | 170000                 | 1.20 |
| 5.1183             | 8.5000  | 4.8750  | 4.8750                    |  |                                      |                                     |                                     | 22300                                 | 18500                                 | 39800                                  |                        |      |

| Part Number |       | Dimensions                 |                                      |  |                                      | Geometry Factors |                |                | Bearing Weight |
|-------------|-------|----------------------------|--------------------------------------|--|--------------------------------------|------------------|----------------|----------------|----------------|
| Inner       | Outer | Max Shaft Fillet Radius BH | Backing Shoulder Dia. e <sub>1</sub> | Max Housing Fillet Radius r <sup>H</sup> | Backing Shoulder Dia. D <sub>2</sub> | G <sub>1</sub>   | G <sub>2</sub> | C <sub>3</sub> |                |
| mm          | mm    | mm                         | mm                                   | mm                                       | mm                                   |                  |                |                | kg             |
| 74510D      | 74850 | 1.8<br>0.06                | 148.8<br>5.75                        | 2.3<br>0.13                              | 198.8<br>7.72                        | 302.0            | 68.5           | 0.1200         | 13.66<br>36.46 |

## CARATTERISTICHE DEL PRODOTTO

|                  |               |
|------------------|---------------|
| Marchio          | TIMKEN        |
| N° Ean13         | 3663952368726 |
| Diametro interno | 130.005 mm    |
| Diametro esterno | 215.9 mm      |
| Spessore         | 123.825 mm    |
| Imballaggio      | 1             |

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE