


## Cuscinetti conico NA285160-285228D-TIMKEN - NA285160-285228D-TIMKEN

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rulli/conico/na285160-285228d-timken>

**TAPERED ROLLER BEARINGS**  
DOUBLE-ROW • TYPE TNA

**TYPE TNA**



| Bearing Dimensions |         |         |                           | Load Ratings          |                       |                       |                       |                       |                       |                       |                       |  |  |
|--------------------|---------|---------|---------------------------|-----------------------|-----------------------|-----------------------|-----------------------|-----------------------|-----------------------|-----------------------|-----------------------|--|--|
| Bore d             | O.D. D  | Width T | Double Outer Ring Width C | Dynami <sup>(1)</sup> | Factor <sup>(2)</sup> | Factor <sup>(2)</sup> | Factor <sup>(2)</sup> | Dynami <sup>(1)</sup> | Dynami <sup>(1)</sup> | Factor <sup>(2)</sup> | Factor <sup>(2)</sup> |  |  |
| mm                 | mm      | mm      | mm                        | C <sub>10</sub>       | e                     | Y <sub>1</sub>        | Y <sub>2</sub>        | C <sub>10</sub>       | C <sub>90</sub>       | C <sub>50</sub>       | K                     |  |  |
| 406.406            | 574.675 | 157.162 | 196.362                   | 100000                | 0.50                  | 1.38                  | 2.02                  | 281000                | 245000                | 500000                | 1.17                  |  |  |
| 16.000             | 22.6250 | 6.1875  | 4.1875                    | 430000                |                       |                       |                       | 84000                 | 50000                 | 112000                |                       |  |  |

| Part Number |         | Shaft                                    |                                      |  |                                      | Housing        |                |                |        | Pin | Bearing Weight |
|-------------|---------|--|--------------------------------------|--|--------------------------------------|----------------|----------------|----------------|--------|-----|----------------|
| Inner       | Outer   | Max Shaft Fillet Radius R <sup>(4)</sup> | Backing Shoulder Dia. d <sub>s</sub> | Max Housing Fillet Radius r <sup>(5)</sup> | Backing Shoulder Dia. D <sub>s</sub> | K <sub>a</sub> | K <sub>b</sub> | K <sub>c</sub> |        |     |                |
| mm          | mm      | mm                                       | mm                                   | mm   | mm                                   | mm             | mm             | mm             | kg     |     |                |
| NA285160    | 285228D | 6.4                                      | 443.8                                | 1.5  | 204.0                                | -              | -              | -              | 112.78 |     |                |
|             |         | 0.25                                     | 17.36                                | 0.06                                       | 21.02                                | -              | -              | -              | 248.66 |     |                |

### CARATTERISTICHE DEL PRODOTTO

|                  |               |
|------------------|---------------|
| Marchio          | TIMKEN        |
| N° Ean13         | 3663952374529 |
| Diametro interno | 406.4 mm      |
| Diametro esterno | 574.675 mm    |
| Spessore         | 157.162 mm    |
| Imballaggio      | 1             |

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE