


Cuscinetti a rullini GBRI102216-IKO - GBRI102216-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/rullini/gbri102216-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			d	D	C	B	F _w
15.875 (5/8)	GBRI 102216	133	15.875 ₀ ⁰ ₀	34.925 ₀ ⁰ ₀	25.400 ₀ ⁰ ₀	25.650	22.225 ₀ ⁰ ₀

Standard mounting dimensions mm		Basic dynamic load rating C ₀ N	Static load rating C ₀ N	Allowable rotational speed (1) rpm	Assembled inner ring LRBZ 101416		
d _a Min.	D _a Max.						
21	21.2	30	0.6	38 300	58 300	7 000	

Notes: (1) Maximum permissible corner radius of the housing.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. No grease is pre-packed. Perform proper lubrication.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952377407
Diametro interno	15.875 mm
Diametro interno	5/8" inch
Diametro esterno	34.925 mm
Diametro esterno	1 3/8" inch
Spessore	25.65 mm
Spessore	1.01" inch
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE