


## Cuscinetti a rullini GBRI122412-IKO - GBRI122412-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/rullini/gbri122412-iko>

IKO  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			d	D	C	B	F <sub>w</sub>
19.050 (3/4)	GBRI 122412	112	19.050 <sup>(1)</sup> <sub>0</sub>	38.100 <sup>(1)</sup> <sub>0</sub>	19.050 <sup>(1)</sup> <sub>0</sub>	19.300	25.400 <sup>(1)</sup> <sub>0</sub>
Standard mounting dimensions mm		Ball diam. mm C	Basic load rating N	Dynamic load rating C <sub>0</sub> N	Allowable rotational speed <sup>(2)</sup> rpm	Assembled inner ring	
d <sub>s</sub> Min.	d <sub>s</sub> Max.					D <sub>s</sub> Max.	r <sub>as max</sub> (°)
24	24.4	33.3	0.6	31 000	46 100	6 000	

Notes:<sup>(1)</sup> Maximum permissible corner radius of the housing.  
<sup>(2)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remarks:  
1. The outer ring has an oil groove and an oil hole.  
2. No grease is preapplied. Perform proper lubrication.

## CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952377414
Diametro interno	19.05 mm
Diametro esterno	38.1 mm
Spessore	19.3 mm
Imballaggio	1

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE