


Cuscinetti a rullini GBRI142616-IKO - GBRI142616-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/rullini/gbri142616-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			d	D	C	B	F_w
22.225 ($\frac{9}{16}$)	GBRI 142616	167	22.225 $\frac{0}{10}$	41.275 $\frac{0}{10}$	25.400 $\frac{0}{10}$	25.650	28.575 $\frac{0}{10}$
Standard mounting dimensions mm		Basic dynamic load rating C_0 N	Limiting load rating C_L N	Allowable rotational speed ^(*) rpm	Assembled inner ring		
d_a Min.	D_a Max.				$r_{as max}$ (¹)		
27	27.5	36.3	0.6	43 900	75 300	5 500	LRBZ 141816

Notes: ⁽¹⁾ Maximum permissible corner radius of the housing.
^(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. No grease is pre-packed. Perform proper lubrication.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952377438
Diametro interno	22.225 mm
Diametro esterno	41.275 mm
Spessore	25.65 mm
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE