


Cuscinetti a rullini GBR1223520-IKO - GBR1223520-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/rullini/gbri223520-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			<i>d</i>	<i>D</i>	<i>C</i>	<i>B</i>	<i>F_w</i>
34.925 (1 3/8)	GBR1 223520	316	34.925 ± 0.015	55.562 ± 0.025	31.750 ± 0.025	32.000	41.275 ± 0.025

Standard mounting dimensions mm		Basic dynamic load rating <i>C</i>	Limiting static load rating <i>C₀</i>	Allowable rotational speed (1) <i>N</i>	Assembled inner ring		
<i>d_a</i>	<i>D_a</i>						
Min.	Max.	<i>r_{sm}</i> max (°)	<i>N</i>	<i>N</i>			
40.2	40.2	50.5	0.6	67 000	130 000	3 500	LRBZ 222620

Notes: (1) Maximum permissible corner radius of the housing.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. No grease is preapplied. Perform proper lubrication.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952377490
Diametro interno	34.925 mm
Diametro esterno	55.562 mm
Spessore	32 mm
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE