


Cuscinetti a rullini GBR101812-IKO - GBR101812-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/rullini/gbr101812-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (ref.) g	Boundary dimensions mm(inch)			Standard mounting dimensions mm ⁽¹⁾	
			F _d	D	C	D _s Max.	r _{as} max
15.875 (5/8)	GBR 101812	55.5	15.875 ⁽²⁾	28.575 ^(1/2)	19.050 ^(3/4)	24.5	0.6
Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽⁴⁾					
N	N	rpm					
23 500	28 500	9 500					

Notes:
(1) Maximum permissible corner radius of the housing.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks:
2. The outer ring has an oil groove and an oil hole.
3. No grease is pre-applied. Perform proper lubrication.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952377698
Diametro interno	15.875 mm
Diametro interno	5/8" inch
Diametro esterno	28.575 mm
Diametro esterno	1 1/8" inch
Spessore	19.05 mm
Spessore	3/4" inch
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE