


## Cuscinetti a rullini GBR182616-IKO - GBR182616-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/rullini/gbr182616-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (ref.) g	Boundary dimensions mm(inch)			Standard mounting dimensions mm ( <sup>(1)</sup> )	
			F <sub>o</sub>	D	C	D <sub>s</sub> Max.	r <sub>as</sub> max
<b>28.575</b> (1 1/8)	<b>GBR 182616</b>	117	28.575( <sup>(1)</sup> / <sub>2</sub> )	41.275(1 1/2)	25.400(1)	36.3	0.6
Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed <sup>(2)</sup>					
N	N	rpm					
43 900	75 300	5 500					

Notes:<sup>(1)</sup> Maximum permissible corner radius of the housing.  
<sup>(2)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remarks:  
1. The outer ring has an oil groove and an oil hole.  
2. No grease is pre-packed. Perform proper lubrication.

## CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952377759
Diametro interno	28.575 mm
Diametro interno	1 1/8" inch
Diametro esterno	41.275 mm
Diametro esterno	1 5/8" inch
Spessore	25.4 mm
Spessore	1" inch
Imballaggio	1

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE