


Cuscinetti a rullini GBR202816-IKO - GBR202816-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/rullini/gbr202816-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



| Shaft dia. mm (inch) | Identification number | Mass (ref.) g | Boundary dimensions mm(inch) | | | Standard mounting dimensions mm ⁽¹⁾ | |
|-----------------------------------|---|---|------------------------------|---------------|-----------|---|---------------------|
| | | | F | D | C | D _s Max. | r _{as max} |
| 31.750 (1 1/4) | GBR 202816 | 128 | 31.750(1 1/4) | 44.450(1 3/4) | 25.400(1) | 39.6 | 0.6 |
| Basic dynamic load rating C | Basic static load rating C ₀ | Allowable rotational speed ⁽²⁾ | | | | | |
| N | N | rpm | | | | | |
| 46 600 | 83 900 | 4 500 | | | | | |

Notes:⁽¹⁾ Maximum permissible corner radius of the housing.
⁽²⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks:
1. The outer ring has an oil groove and an oil hole.
2. No grease is pre-packed. Perform proper lubrication.

CARATTERISTICHE DEL PRODOTTO

| | |
|------------------|------------------|
| Marchio | IKO |
| N° Ean13 | 3663952377766 |
| Diametro interno | 31.75 mm |
| Diametro esterno | 44.45 mm |
| Spessore | 25.4 mm |
| Peso | 133 g |
| Imballaggio | 1 |
| Standard | Nessuno standard |

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE