


## Cuscinetti a rullini GBRI406028-IKO - GBRI406028-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/rullini/gbri406028-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)					
			$d$	$D$	$C$	$B$	$F_w$	
<b>63.500</b> (2 1/2)	<b>GBRI 406028</b>	1 230	63.500 $\pm$ 0.010	95.250 $\pm$ 0.010	44.450 $\pm$ 0.010	44.700	76.200 $\pm$ 0.010	
Standard mounting dimensions mm		Ball diam. mm (inch)	Basic dynamic load rating $C_0$ N	Allowable rotational speed <sup>(*)</sup> rpm	Assembled inner ring			
$d_a$ Min.	$D_a$ Max.				$r_{as\ max}$ Max.			
71	73	88	154 000	368 000	2 000	<b>LRBZ 404828</b>		

Notes: <sup>(\*)</sup> Maximum permissible corner radius of the housing.  
<sup>(\*)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remarks: 1. The outer ring has an oil groove and an oil hole.  
2. No grease is pre-applied. Perform proper lubrication.

## CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952377940
Diametro interno	63.5 mm
Diametro esterno	95.25 mm
Spessore	44.45 mm
Imballaggio	1

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE