



Cuscinetti a rullini RNA6903-U-IKO - RNA6903-U-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/rullini/rna6903-u-iko>



MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring



Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		F_w	D	C	r_f ⁽¹⁾
22	—	—	—	RNA 6903U	40.5	22	30	23	0.3
Standard rounding dimension D_s Max. mm	Basic dynamic load rating C		Basic static load rating C_0		Allowable rotational speed ⁽²⁾				
28	19 800		30 600		8 500				

Notes: ⁽¹⁾ Minimum allowable value of chamfer dimension r .
⁽²⁾ Allowable rotational speed applies to grease lubrication.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952378923
Diametro interno	22 mm
Diametro esterno	30 mm
Spessore	23 mm
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE