

## Cuscinetti a rullini RNA49-22-U-IKO - RNA49-22-U-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/rullini/rna49-22-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, Without Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		$F_w$	$D$	$C$	$r_s$ (1)
<b>28</b>	---	<b>RNA 49/22U</b>	---	---	55.5	28	39	17	0.3
Standard rounding dimension $D_s$ Max. mm		Basic dynamic load rating $C$ N	Basic static load rating $C_0$ N	Allowable rotational speed (grease) rpm					
37		18 300	23 700	7 000					

Notes: (1) Minimum allowable value of chamfer dimension  $r$ .  
(2) Allowable rotational speed applies to grease lubrication.  
Remarks: 1. The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952378985
Diametro interno	28 mm
Diametro interno	1.102" inch
Diametro esterno	39 mm
Diametro esterno	1.535" inch
Spessore	17 mm
Spessore	0.669" inch
Imballaggio	1

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE