

## Cuscinetti a rullini RNA6912-UU-IKO - RNA6912-UU-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/rullini/rna6912-uu-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, Without Inner Ring

Shaft dia. mm	Identification number				Mass (Ref) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		$F_w$	$D$	$C$	$r_s$ (1)
68	—	—	<b>RNA6912UU</b>	—	505	68	85	45	1
Standard mounting dimension $D_s$ Max. mm									
Basic dynamic load rating $C$	N	N	N	N					
Basic static load rating $C_0$									
Allowable hydraulic speed (2)									
80	93 400	186 000	3 000						

Notes: (1) Minimum allowable value of chamfer dimension  $r$ .  
(2) Allowable rotational speed applies to grease lubrication.  
Remarks: 1. The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952379500
Diametro interno	68 mm
Diametro interno	2.677" inch
Diametro esterno	85 mm
Diametro esterno	3.346" inch
Spessore	45 mm
Spessore	1.772" inch
Imballaggio	1

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE