

Cuscinetti a rullini RNA6919-UU-IKO - RNA6919-UU-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/rullini/rna6919-uu-iko>

I KO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring

Shaft dia. mm	Identification number				Mass (Ref) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		F_w	D	C	r_s (1)
110	—	—	RNA 6919UU	—	1 420	110	130	63	1.1
Standard mounting dimension D_s Max. mm									
	Basic dynamic load rating C	Basic static load rating C_0	Allowable rotational speed (2)						
123.5	177 000	493 000	1 700						

Notes: (1) Minimum allowable value of chamfer dimension r .
(2) Allowable rotational speed applies to grease lubrication.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARATTERISTICHE DEL PRODOTTO

Marchio	I KO
N° Ean13	3663952379838
Diametro interno	110 mm
Diametro esterno	130 mm
Spessore	63 mm
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE