


## Cuscinetti a rullini RNA4924-UU-IKO - RNA4924-UU-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/rullini/rna4924-uu-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, Without Inner Ring



Shaft dia. mm	Identification number				Mass (Ref) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		F <sub>w</sub>	D	C	7 <sub>s</sub> (1)
135	<b>RNA 4924UU</b>	—	—	—	1 940	135	165	45	1.1
Standard mounting diameter D <sub>s</sub> Max. mm	Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed (2)						
158.5	178 000	410 000	1 400						

Notes: (1) Minimum allowable value of chamfer dimension r.  
(2) Allowable rotational speed applies to grease lubrication.  
Remarks: 1. The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

## CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952379906
Diametro interno	135 mm
Diametro interno	5.315" inch
Diametro esterno	165 mm
Diametro esterno	6.496" inch
Spessore	45 mm
Spessore	1.772" inch
Imballaggio	1

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE