

Cuscinetti a rullini NA6903-U-IKO - NA6903-U-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/rullini/na6903-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm				
	With two seals	With one seal	With two seals	With one seal		d	D	C	B	
17	—	—	—	—	NA 6903U	68.5	17	30	23	24

r _s min ⁽¹⁾ F _w	Standard mounting dimensions mm			Basic static load rating C ₀	Basic dynamic load rating C	Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring LRTZ 172224
	Min.	Max.	Max.				
0.3	22	19	21	28	19 800	30 600	8 500

Notes: (1) Minimum allowable value of shaft diameter r.
(2) Allowable rotational speed applies to grease lubrication.
Remark: This roller ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952381206
Diametro interno	17 mm
Diametro esterno	30 mm
Spessore	24 mm
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE