


Cuscinetti a rullini
NA6909-U-IKO - NA6909-U-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/rullini/na6909-u-iko>

**MACHINED TYPE NEEDLE ROLLER BEARINGS**
With Seal, With Inner Ring



Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		d	D	C	B
45	—	—	—	NA 6909U	520	45	68	40	41

r_s mm (1)	F_w	Standard mounting dimensions mm		d_s Min.	D_s Max.	Basic rating C	Basic load rating C ₀	Allowable rotational speed (2)	Assembled inner ring
		Min.	Max.						
0.6	52	49	51	64	66 600	127 000	N	3 500	LRTZ 455241

Notes (1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to grease lubrication.
Remark: 1. The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952381558
Diametro interno	45 mm
Diametro esterno	68 mm
Spessore	41 mm
Imballaggio	1

contatto@123cuscinetti.it
+33 3 59 36 04 90
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE