


## Cuscinetti a rullini NA4912-U-IKO - NA4912-U-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/rullini/na4912-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring



Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		d	D	C	B
60	—	NA 4912U	—	—	445	60	85	25	26

r <sub>s</sub> min (1)	F <sub>w</sub>	Standard mounting dimensions mm			Basic static load rating C <sub>0</sub> N	Allowable rotational speed <sup>(2)</sup> rpm	Assembled inner ring	
		d <sub>s</sub> Min.	d <sub>s</sub> Max.	D <sub>s</sub> Max.				
1	68	65	66	80	54 500	92 800	3 000	LRTZ 606826

Notes: (1) Minimum allowable value of shaft diameter r.  
(2) Allowable rotational speed applies to grease lubrication.  
Remark: The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

## CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952381664
Diametro interno	60 mm
Diametro esterno	85 mm
Spessore	26 mm
Imballaggio	1

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE