

Cuscinetti a rullini NA6915-UU-IKO - NA6915-UU-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/rullini/na6915-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring

| Shaft dia. mm | Identification number | | | | Mass (Ref.) g | Boundary dimensions mm | | | |
|------------------|-----------------------|---------------|----------------|---------------|---------------------|---------------------------|-----|----|----|
| | With two seals | With one seal | With two seals | With one seal | | d | D | C | B |
| 75 | — | — | NA 6915UU | — | 1 480 | 75 | 105 | 54 | 55 |

| r _s min (1) | F _w | Standard mounting dimensions mm | | | Basic static load rating C ₀ N | Basic dynamic load rating C ₁₀ N | Allowable rotational speed ⁽²⁾ rpm | Assembled inner ring |
|---------------------------|----------------|------------------------------------|---------------------|---------------------|---|---|--|----------------------|
| | | d _s Min. | d _s Max. | D _s Max. | | | | |
| 1 | 85 | 80 | 83 | 100 | 128 000 | 299 000 | 2 000 | LRTZ 758555 |

Notes: (1) Minimum allowable value of shaft dimension r
(2) Allowable rotational speed applies to grease lubrication.
Remark: This outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARATTERISTICHE DEL PRODOTTO

| | |
|------------------|---------------|
| Marchio | IKO |
| N° Ean13 | 3663952381800 |
| Diametro interno | 75 mm |
| Diametro esterno | 105 mm |
| Spessore | 55 mm |
| Imballaggio | 1 |

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE