

Cuscinetti a rullini NA6919-U-IKO - NA6919-U-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/rullini/na6919-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm				
	With two seals	With one seal	With two seals	With one seal		d	D	C	B	
95	—	—	—	—	NA 6919U	2 600	95	130	63	64

r_s mm	F_w	Standard mounting dimensions mm		Basic static load rating C ₀	Basic dynamic load rating C	Allowable rotational speed ⁽¹⁾ rpm	Assembled inner ring	
		Min.	Max.					
1.1	110	101.5	108	123.5	177 000	493 000	1 700	LRTZ 9511064

Notes: (1) Minimum allowable value of shaft diameter r .
(2) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952381954
Diametro interno	95 mm
Diametro esterno	130 mm
Spessore	64 mm
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE