

## Cuscinetti a rullini NA4920-U-IKO - NA4920-U-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/rullini/na4920-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		d	D	C	B
100	—	NA 4920U	—	—	1 980	100	140	40	41

r <sub>s</sub> min <sup>(1)</sup> F <sub>w</sub>	Standard mounting dimensions mm		Basic static load rating C <sub>0</sub> N	Basic dynamic load rating C <sub>10</sub> N	Allowable rotational speed <sup>(2)</sup> rpm	Assembled inner ring LRTZ 10011541		
	Min.	Max.						
1.1	115	106.5	113	133.5	134 000	297 000	1 700	

Notes: (1) Minimum allowable value of shaft dimension r.  
(2) Allowable rotational speed applies to grease lubrication.  
Remark: This outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

## CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952381985
Diametro interno	100 mm
Diametro esterno	140 mm
Spessore	41 mm
Imballaggio	1

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE