


Cuscinetti a rullini BR364828-U-IKO - BR364828-U-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/rullini/br364828-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Max. (Ref.) g	Boundary dimensions mm(inch)		
	With two seals	With one seal		F_w	D	C
57.150 (2 1/4)		BR 364828 U	459	57.150 (2 1/4)	76.200 (3)	44.450 (1 3/4)
Standard mounting dimensions mm		Basic dynamic load rating	Static load rating	Allowable rotational speed ⁽²⁾		
D_1	$F_{a \max}$ ⁽¹⁾	C	C_0	rpm		
Max.		N	N			
69.0	1.5	90 300	158 000	3 500		

Notes: (1) Minimum allowable value of chamfer dimension r .
(2) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952382333
Diametro interno	57.15 mm
Diametro esterno	76.2 mm
Spessore	44.45 mm
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE