


Cuscinetti a rullini BR486028-U-IKO - BR486028-U-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/rullini/br486028-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring, Inch Series



| Shaft dia. mm (inch) | Identification number | | Mass (Ref.) g | Boundary dimensions mm(inch) | | |
|---------------------------------|-----------------------|---------------------------|---------------------|---|----------------|----------------|
| | With two seals | With one seal | | F_w | D | C |
| 76.200 (3) | | BR 486028 U | 585 | 76.200 (3) | 95.250 (3 7/8) | 44.450 (1 3/4) |
| Standard mounting dimensions mm | | Basic dynamic load rating | Static load rating | Allowable rotational speed ⁽²⁾ | | |
| D_1 Max. | r_{as} max | C | C_0 | N | N | rpm |
| 87.0 | 2.0 | 105 000 | 211 000 | | | 2 500 |

Notes: (1) Minimum allowable value of chamfer dimension r .
(2) Allowable rotational speed applies to grease lubrication.
Remark: This roller ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARATTERISTICHE DEL PRODOTTO

| | |
|------------------|---------------|
| Marchio | IKO |
| N° Ean13 | 3663952382388 |
| Diametro interno | 76.2 mm |
| Diametro esterno | 95.25 mm |
| Spessore | 44.45 mm |
| Imballaggio | 1 |

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE