


Cuscinetti a rullini BRI142620-UU-IKO - BRI142620-UU-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/rullini/bri142620-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring, Inch Series



| Shaft dia. mm (inch) | Identification number | | Mass (Ref.) g | Boundary dimensions mm(inch) | | | |
|------------------------------------|-----------------------------------|---------------|-----------------------------|-------------------------------------|----------------------------------------|--------------------------------------------------|---------------------------------------|
| | With two seals | With one seal | | d | D | C | B |
| 22.225 ($\frac{3}{4}$) | BRI 142620 UU | | 177 | 22.225 ($1 \frac{1}{4}$) | 41.275 ($1 \frac{3}{4}$) | 31.750 ($1 \frac{1}{4}$) | 32.000 |
| F_w | Standard mounting dimensions (mm) | | | Basic dynamic load rating C N | Basic static load rating C_0 N | Allowable rotational speed ^(*) rpm | Assembled inner ring LRBZ 141820 B |
| | Min. | Max. | Max. as max. ^(*) | | | | |
| 28.575 ($1 \frac{1}{4}$) | 27 | 27.5 | 36.0 | 34 900 | 49 900 | 7 000 | |

Notes: (*) Minimum allowable value of diameter dimension r
(**) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARATTERISTICHE DEL PRODOTTO

| | |
|------------------|---------------|
| Marchio | IKO |
| N° Ean13 | 3663952382548 |
| Diametro interno | 22.225 mm |
| Diametro esterno | 41.275 mm |
| Spessore | 31.75 mm |
| Imballaggio | 1 |

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE