


## Cuscinetti a rullini BRI142620-U-IKO - BRI142620-U-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/rullini/bri142620-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)				
	With two seals	With one seal		d	D	C	B	
<b>22.225</b> ( $\frac{9}{4}$ )		<b>BRI 142620 U</b>	177	22.225 ( $1 \frac{1}{4}$ )	41.275 ( $1 \frac{5}{8}$ )	31.750 ( $1 \frac{1}{4}$ )	32.000	
$F_w$	Standard mounting dimensions (mm)			Basic dynamic load rating C N	Basic static load rating $C_0$ N	Allowable rotational speed <sup>(*)</sup> rpm	Assembled inner ring LRBZ 141820 B	
	Min.	Max.	Misg. as max. <sup>(*)</sup>					
	27	27.5	36.0	34 900	49 900	7 000		

Notes: (\*) Minimum allowable value of chamfer dimension r.  
(\*\*) Allowable rotational speed applies to grease lubrication.  
Remark: The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952382555
Diametro interno	22.225 mm
Diametro esterno	41.275 mm
Spessore	31.75 mm
Imballaggio	1

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE