


Cuscinetti a rullini BRI223520-U-IKO - BRI223520-U-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/rullini/bri223520-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)			
	With two seals	With one seal		d	D	C	B
34.925 (1 3/8)		BRI 223520 U	275	34.925 (1 3/8)	55.562 (2 1/8)	31.750 (1 1/4)	32.000
F_w	Standard mounting dimensions (mm)			Basic dynamic load rating C N	Basic static load rating C_0 N	Allowable rotational speed ^(*) rpm	Assembled inner ring LRBZ 222620 B
	Min.	Max.	D_a Max. as max. ^(*)				
	40.2	40.2	48.3	44 800	70 900	4 500	

Notes: (*) Minimum allowable value of chamfer dimension r.
(**) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952382630
Diametro interno	34.925 mm
Diametro esterno	55.562 mm
Spessore	31.75 mm
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE