

Cuscinetti a rullini BRI325228-UU-IKO - BRI325228-UU-IKO

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/rullini/bri325228-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring, Inch Series

| Shaft dia. mm (inch) | Identification number | | Mass (Ref.) g | Boundary dimensions mm(inch) | | | | |
|----------------------------|-----------------------------------|---------------|-----------------------------|-------------------------------------|--|--|---------------------------------------|--|
| | With two seals | With one seal | | d | D | C | B | |
| 50.800 (2) | BRI 325228 UU | | 889 | 50.800 (2) | 82.550 (3 $\frac{1}{4}$) | 44.450 (1 $\frac{3}{4}$) | 44.700 | |
| F_w | Standard mounting dimensions (mm) | | | Basic dynamic load rating C N | Basic static load rating C_0 N | Allowable rotational speed ^(*) rpm | Assembled inner ring LRBZ 324028 B | |
| | Min. | Max. | Max. as max. ^(*) | | | | | |
| 63.500 (2 $\frac{1}{2}$) | 58 | 61 | 74.3 | 1.5 | 94 600 | 174 000 | 3 000 | |

Notes: (*) Minimum allowable value of diameter dimension r.
(**) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARATTERISTICHE DEL PRODOTTO

| | |
|------------------|---------------|
| Marchio | IKO |
| N° Ean13 | 3663952382739 |
| Diametro interno | 50.8 mm |
| Diametro esterno | 82.55 mm |
| Spessore | 44.45 mm |
| Imballaggio | 1 |

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE